

15PLB76 8 Ω

Woofer

- 800 W continuous program power capacity
- 76 mm (3 in) copper voice coil
- 40 - 2000 Hz response
- 100 dB sensitivity



15PLB76 8 Ω

Woofer

SPECIFICATIONS

Nominal Diameter	380 mm (15 in)
Nominal Impedance	8 Ω
Minimum Impedance	6.2 Ω
Nominal Power Handling	400 W
2 hours test made with continuous pink noise signal within the range Fs-10Fs. Power calculated on rated minimum impedance. Loudspeaker in free air.	
Continuous Power Handling	800 W
Power on Continuous Program is defined as 3 dB greater than the Nominal rating.	
Sensitivity	100 dB
Applied RMS Voltage is set to 2.83 V for 8 ohms Nominal Impedance.	
Frequency Range	40 Hz - 2000 Hz
Voice Coil Diameter	76 mm (3 in)
Winding Material	Copper
Former Material	Glass Fibre
Winding Depth	16 mm (0.62 in)
Magnetic Gap Depth	11 mm (0.4 in)
Flux Density	1.15 T
Woofer Cone Treatment	TWP Waterproof Both Sides

PARAMETERS

Thiele-Small parameters are measured after a high level 20 Hz sine wave preconditioning test.

Fs	42 Hz
Re	5 Ω
Qes	0.26
Qms	5.9
Qts	0.25
Vas	164 dm³ (5.8 ft³)
Sd	855 cm² (132.5 in²)
η0	4.5 %
Xmax	5 mm
Xvar	8 mm
Mms	88 g
Bl	22.1 Tm
Le	1.3 mH
EBP	162 Hz

DESIGN



Surround Shape	Triple Roll
Cone Shape	Exponential
Magnet Material	Ferrite
Spider	Single
Pole Design	T-Pole
Woofer Cone Treatment	TWP Waterproof Both Sides
Recommended Enclosure	100 dm³ (3.53 ft³)
Recommended Tuning	50 Hz


MOUNTING AND SHIPPING INFO

Overall Diameter	393 mm (15.5 in)
Bolt Circle Diameter	374 mm (14.7 in)
Baffle Cutout Diameter	354 mm (13.9 in)
Depth	169 mm (6.65 in)
Flange and Gasket Thickness	16 mm (0.62 in)
Air Volume Occupied by Driver	5.2 dm³ (0.18 ft³)
Net Weight	8.6 kg (18.96 lb)
Shipping Units	1 pcs
Shipping Weight	9.9 kg (21.83 lb)
Shipping Box	425x425x224 mm (16.73x16.73x8.82 in)

SERVICE KITS

LF recone-kits	RCK15PLB768
----------------	--------------------





Model: **15 PLB 76**
Enclosure Type: **Bass Reflex**

Internal Net Volume (Liters): **100**
Tuning Frequency (Hz): **50** *Port Area (cm²):* **222,3**
Frequency (-3 dB) (Hz): **53,5** *Port Length (cm):* **12,0**

Excursion Limited Maximum SPL at 1 meter (dB): **123,1** equal to **312,2** Watts (*Bass Band Power Rating*)
Thermal Limited Maximum SPL at 1 meter (dB): **124,1** equal to **400,0** Watts (*Mid Band Power Rating*)



LF Drivers

Ø 15 inches

15PLB76 8 Ω

Woofer



Professional loudspeaker transducers since 1946

B&C Speakers S.p.A. Via Poggiomoro, 1 - Loc. Vallina, 50012 Bagno a Ripoli (FI) | ITALY
Tel. +39 055 65721 | Fax +39 055 6572312 | mail@bcspeakers.com