

## DE550 16 Ω

### SPECIFICATIONS

Driver mounted on B&C ME 45 horn.

Throat Diameter	<b>25 mm (1 in)</b>
Nominal Impedance	<b>16 Ω</b>
Minimum Impedance	<b>13.3 Ω</b>
Nominal Power Handling	<b>70 W</b>
2 hour test made with continuous pink noise signal within the range from the recommended crossover frequency to 20 kHz. Power calculated on rated minimum impedance.	
Continuous Power Handling	<b>140 W</b>
Power on Continuous Program is defined as 3 dB greater than the Nominal rating.	
Sensitivity	<b>109 dB</b>
Applied RMS Voltage is set to 4 V for 16 ohms Nominal Impedance.	
Frequency Range	<b>1 kHz - 17 kHz</b>
Recommended Crossover	<b>1.2 kHz</b>
12 dB/oct. or higher slope high-pass filter.	
Voice Coil Diameter	<b>51 mm (2 in)</b>
Winding Material	<b>Aluminium</b>
Inductance	<b>0.14 mH</b>
Flux Density	<b>2 T</b>
Diaphragm Material	<b>HT Polymer</b>

140 W continuous program power capacity  
 1" horn throat diameter  
 51 mm (2 in) aluminium voice coil  
 HT Polymer diaphragm  
 1000 - 17000 Hz response  
 109 dB sensitivity

### MOUNTING AND SHIPPING INFO

Two M6 holes 180° on 76 mm (3 in) diameter



Overall Diameter	<b>92 mm (3.62 in)</b>
Depth	<b>49 mm (1.93 in)</b>
Net Weight	<b>1.17 kg (2.57 lb)</b>
Shipping Units	<b>1 pcs</b>
Shipping Weight	<b>1.2 kg (2.63 lb)</b>
Shipping Box	<b>105x105x65 mm</b> <b>(4.13x4.13x2.56 in)</b>

### SERVICE KITS

HF replacement-diaphragm	<b>MMD55016</b>
--------------------------	-----------------



## DE550 16 Ω



## DE550 16 Ω

